## (19) World Intellectual Property Organization

International Bureau



# 

### (43) International Publication Date 22 September 2005 (22.09.2005)

### (10) International Publication Number WO 2005/088277 A1

(51) International Patent Classification7:

G01N 21/55

(21) International Application Number:

PCT/GB2005/050033

- (22) International Filing Date: 15 March 2005 (15.03.2005)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 0405815.2

15 March 2004 (15.03.2004)

- (71) Applicant (for all designated States except US): EVANESCO LIMITED [GB/GB]; Forde Courte, Forde Road, Newton Abbot TQ12 4AD (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): SHAW, Andrew Mark [GB/GB]; 8 Trehill House, Kenn, Exeter Devon EX6 7XJ
- (74) Agent: Marks & Clerk; 66-68 Hills Road, Cambridge Cambridgeshire CB2 1LA (GB).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM. ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available); ARIPO (BW. GH. GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

### Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of

[Continued on next page]

(54) Title: EVANESCENT WAVE SENSING APPARATUS AND METHODS USING PLASMONS



that light within said cavity makes a plurality of passes between said surfaces, an optical path between said surfaces including a reflection from a totally internally reflecting (TIR) surface, said reflection from said TIR surface generating an evanescent wave to provide a sensing function; a light source to inject light into said cavity; and a detector to detect a light level within said cavity; and wherein said TTR surface is provided with an electrically conducting material over at least part of said TTR surface such that said evanescent wave excites a plasmon within said material; whereby a change in absorption of said evanescent wave due to a change in said plasmon excitation is detectable using said detector to provide said sensing function.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.